


# Short pitch precision roller chains (B series)

## Zinc Plated

Duplex roller chains & bush chains

Part nr.	DIN/ISO 606 Chain no.	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length	Inner plate depth	Plate thickness	Transverse pitch	
		P	d1 max	b1 min	d2 max	L max	Lc max	h2 max	T max	Pt
		mm	mm	mm	mm	mm	mm	mm	mm	mm
10004B-2ZP	04B-2ZP	6,000	4,00	2,80	1,85	13,2	14,2	5,00	0,60	5,50
10005B-2ZP	05B-2ZP	8,000	5,00	3,00	2,31	13,9	14,5	7,10	0,80	5,64
10006B-2ZP	*06B-2ZP	9,525	6,35	5,72	3,28	23,4	24,4	8,20	1,30	10,24
10008B-2ZP	08B-2ZP	12,700	8,51	7,75	4,45	31,0	32,2	11,80	1,60	13,92
10010B-2ZP	10B-2ZP	15,875	10,16	9,65	5,08	36,1	37,5	14,70	1,70	16,59
10012B-2ZP	12B-2ZP	19,050	12,07	11,68	5,72	42,0	43,6	16,00	1,85	19,46
10016B-2ZP	16B-2ZP	25,400	15,88	17,02	8,28	68,0	69,3	21,00	4,15/3,1	31,88
10020B-2ZP	20B-2ZP	31,750	19,05	19,56	10,19	77,8	81,5	26,40	4,50/3,5	36,45
10024B-2ZP	24B-2ZP	38,100	25,40	25,40	14,63	101,7	106,2	33,20	6,00/4,8	48,36
10028B-2ZP	28B-2ZP	44,450	27,94	30,99	15,90	124,6	129,1	36,70	7,50/6,0	59,56
10032B-2ZP	32B-2ZP	50,800	29,21	30,99	17,81	124,6	129,6	42,00	7,00/6,0	58,55
10040B-2ZP	40B-2ZP	63,500	39,37	38,10	22,89	154,5	161,5	52,96	8,50/8,0	72,29
10048B-2ZP	48B-2ZP	76,200	48,26	45,72	29,24	190,4	198,2	63,80	12,00/10,0	91,21
10056B-2ZP	56B-2ZP	88,900	53,98	53,34	34,32	221,2	229,6	77,80	13,50/12,0	106,60
10064B-2ZP	64B-2ZP	101,600	63,50	60,96	39,40	249,9	258,4	90,17	15,00/13,0	119,89
10072B-2ZP	72B-2ZP	114,300	72,39	68,58	44,48	283,7	292,7	103,60	17,00/15,0	136,27

\* Straight side plates



Ultimate tensile strength	Average tensile strength	Weight per meter	Available chain parts				
Q min	Q0	q	E	S	L	C	A
kN/lbf	kN	kg/m					
5,0/1124	6,1	0,23	X		X	X	X
7,8/1773	10,2	0,33	X		X	X	X
16,9/3841	18,7	0,77	X		X	X	X
32,0/7273	38,7	1,34	X	X	X	X	X
44,5/10114	56,2	1,84	X	X	X	X	X
57,8/13136	66,1	2,31	X	X	X	X	X
106,0/24091	152,0	5,42	X	X	X	X	X
170,0/38636	229	7,20		X	X		X
280,0/63636	319,2	13,40		X	X		X
360,0/81818	406,8	16,60		X	X		X
450,0/102273	508,5	21,00		X	X		X
630,0/143182	711,9	32,00		X	X		X
1000,0/227272	1130,0	50,00		X	X		X
1600,0/363635	1760,0	71,48		X	X		X
2000,0/454544	2200,0	91,00		X	X		X
2500,0/568180	2750,0	120,40		X	X		X



Donghua Zinc Plated Roller Chains are developed to offer good wear and good corrosion resistance. For special applications we deliver the new developed ZinTek Coating on request. All Donghua roller chains are: Pre-loaded, Fatigue resistant, Wear resistant and Pre-lubricated. Donghua simplex, duplex and triplex roller chains are manufactured according to ISO 606 DIN8187, standard pre-loaded, pre-lubricated, do have seamless rollers and are marked with production batch code number for complete traceability. All Donghua roller chains are sealed in plastic bags and packed in cardboard boxes with clear ISO 606 DIN descriptions and safety instructions. Standard packaging size is 5 meter box, reels are available on request. Cut to length service is available on request. Several test certificates like breaking load, length tolerance and material analyses are possible and available on request. Rollers chains which are needed for 'run as pairs' applications can be matched as pairs on request. DIN, 1/2DIN and 1/3DIN length tolerance are possible, please ask us for a quotation. For high temperature, low temperature, food application or special environments different kind of special lubricants are available. Please ask our sales team for any special needs. For drive chain calculation and right dimension check, please contact our engineering department, also see drive chain calculation data sheet on page 301. By filling this data sheet and sending this to our engineering department you will receive a detailed drive chain calculation including life time expectation. Sprockets are available for all roller chains, with pilot bore, fixed bore, keyway, setscrew or bearing bore with grooves. Standard toothing, hardened toothing or special toothing are possible with pilot bore, fixed bore or taper bush. Chain tools, tensioners and chain lubricants please see page 302-310.

Solution range