


# Short pitch precision roller chains (A series)

Duplex roller chains & bush chains

Part nr.	DIN/ISO 606 Chain no.	ANSI Chain no.	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plate thickness	Transverse pitch
							L max	Lc max			
							P	d1 max			
		mm		mm		mm		mm		mm	
10025-2	*04C-2	*25-2	6,350	3,30	3,18	2,31	14,5	15,0	6,00	0,80	6,40
10035-2	*06C-2	*35-2	9,525	5,08	4,77	3,58	22,5	23,3	9,00	1,30	10,13
10041-1	085-2	41-2	12,700	7,77	6,25	3,58	25,7	26,9	9,91	1,30	11,95
10040-2	08A-2	40-2	12,700	7,95	7,85	3,96	31,0	32,2	12,00	1,50	14,38
10050-2	10A-2	50-2	15,875	10,16	9,40	5,08	38,9	40,4	15,09	2,03	18,11
10060-2	12A-2	60-2	19,050	11,91	12,57	5,94	48,8	50,5	18,00	2,42	22,78
10080-2	16A-2	80-2	25,400	15,88	15,75	7,92	62,7	64,3	24,00	3,25	29,29
100100-2	20A-2	100-2	31,750	19,05	18,90	9,53	76,4	80,5	30,00	4,00	35,76
100120-2	24A-2	120-2	38,100	22,23	25,22	11,10	95,8	99,7	35,70	4,80	45,44
100140-2	28A-2	140-2	44,450	25,40	25,22	12,70	103,3	107,9	41,00	5,60	48,87
100160-2	32A-2	160-2	50,800	28,58	31,55	14,27	123,3	128,1	47,80	6,40	58,55
100180-2	36A-2	180-2	57,150	35,71	35,48	17,46	138,6	144,4	53,60	7,20	65,84
100200-2	40A-2	200-2	63,500	39,68	37,85	19,85	151,9	158,8	60,00	8,00	71,55
100240-2	48A-2	240-2	76,200	47,63	47,35	23,81	183,4	190,8	72,39	9,50	87,83

\* Bush chain: d1 in the table indicates the external diameter of the bush.



Ultimate tensile strength	Average tensile strength	Weight per meter	Available chain parts				
Q min	Q0	q	E	S	L	C	A
kN/lbf	kN	kg/m					
7,00/1591	10,0	0,28	X			X	X
15,80/3591	22,3	0,63	X			X	X
13,34/3032	16,9	0,81	X		X	X	X
28,20/6409	37,2	1,12	X		X	X	X
44,40/10091	62,6	2,00	X		X	X	X
63,60/14455	86,4	2,92	X		X	X	X
113,40/25773	148,6	5,15	X		X	X	X
177,00/40227	215,2	7,80		X	X		X
254,00/57727	326,2	11,70		X	X		X
344,80/78364	445,0	15,14		X	X		X
453,60/103091	533,8	20,14		X	X		X
560,50/127386	722,2	29,22		X	X		X
707,60/160818	933,6	32,24		X	X		X
1020,60/213955	1343,2	45,23		X	X		X

E



S



L



C



A



All Donghua roller chains are: Pre-loaded, Fatigue resistant, Wear resistant and Pre-lubricated. Donghua simplex, duplex and triplex roller chains are manufactured according to ISO 606 DIN8187, standard pre-loaded, pre-lubricated, do have seamless rollers and are marked with production batch code number for complete traceability. All Donghua roller chains are sealed in plastic bags and packed in cardboard boxes with clear ISO 606 DIN descriptions and safety instructions. Standard packaging size is 5 meter box, reels are available on request. Rollers chains which are needed for 'run as pairs' applications can be matched as pairs on request. DIN, 1/2DIN and 1/3DIN length tolerance are possible, please ask us for a quotation. For high temperature, low temperature, food application or special environments different kind of special lubricants are available. Please ask our sales team for any special needs. For drive chain calculation and right dimension check, please contact our engineering department, also see drive chain calculation data sheet on page 301. By filling this data sheet and sending this to our engineering department you will receive a detailed drive chain calculation including life time expectation. Sprockets are available for all roller chains, with pilot bore, fixed bore, keyway, setscrew or bearing bore with grooves. Standard toothing, hardened toothing or special toothing are possible with pilot bore, fixed bore or taper bush. Chain tools, tensioners and chain lubricants please see page 302-310.